



Composite Resource Marine Laminating Resin

Safety Data Sheet CR3010MA Marine Laminating

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/10/2014

Revision date:

Supersedes:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture – liquid resin
Trade name : Composite Resource Marine Laminating Resin
CAS No : Mixture
Product code : CR3010MACP, CR3010MACQ, CR3010MAG
Other means of identification : DISTRIBUTED BY REVCHEM COMPOSITES, INC.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marine Laminating Resin

1.3. Details of the supplier of the safety data sheet

Composite Resources is supplied by Revchem Composites. 2720 South Willow Ave., Bloomington, CA 92316 1-800-281-4975

1.4. Emergency telephone number

Emergency number : 800.424.9300
CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 1 H224
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Carc. 2 H351

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H224 - Extremely flammable liquid and vapour
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H351 - Suspected of causing cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P264 - Wash ... thoroughly after handling
P280 - Wear protective clothing
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P321 - Specific treatment (see ... on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry chemical powder, foam for extinction

Composite Resource Marine Laminating Resin

Safety Data Sheet CR3010MA Marine Laminating

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Proprietary Resin	(CAS No) Proprietary	~ 57	Not classified
Styrene, inhibited	(CAS No) 100-42-5	~ 43.8	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

Composite Resource Marine Laminating Resin

Safety Data Sheet CR3010MA Marine Laminating

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources.
Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

styrene, inhibited (100-42-5)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH STEL (ppm)	40 ppm

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.
Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Respiratory protection : Wear appropriate mask.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear, colorless liquid
Colour : Clear
Odour : Characteristic
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : < 1 slower than ether
Melting point : No data available
Freezing point : No data available
Boiling point : 145.22 °C (293.4 °F) Initial Boiling Point for Styrene @ 760.00 mm HG
Flash point : 31.1 °C for Volatile Component (88 Deg F)
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (Lowest Value of Styrene) : Lower – 1.1%
(Highest Value of Styrene) : Upper – 6.1%
Vapour pressure : 4.3 mm Hg Vapor Pressure for Styrene 20 °C (68 °F)
Relative vapour density at 20 °C : 3.6 (Air = 1)

Composite Resource Marine Laminating Resin

Safety Data Sheet CR3010MA Marine Laminating

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density	: 1.110 - 1.130 Relative Density @ 25 °C (77 °F)
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

styrene, inhibited (100-42-5)	
LD50 oral rat	5000 mg/kg (>6000 mg/kg bodyweight; Rat; Rat)
LD50 dermal rat	2820 mg/kg (>2000 mg/kg bodyweight; Rat; Rat; Experimental value)
LD50 dermal rabbit	5010 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	12 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	2770 ppm/4h (Rat)
ATE CLP (oral)	5000.000 mg/kg
ATE CLP (dermal)	5010.000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	: Suspected of causing cancer.

styrene, inhibited (100-42-5)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
	Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
	Based on available data, the classification criteria are not met

Composite Resource Marine Laminating Resin

Safety Data Sheet CR3010MA Marine Laminating

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
	Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Likely routes of exposure	: Inhalation

SECTION 12: Ecological information

12.1. Toxicity

styrene, inhibited (100-42-5)	
LC50 fishes 1	25 mg/l (96 h; Lepomis macrochirus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	23 mg/l (48 h; Daphnia magna; LOCOMOTOR EFFECT)
LC50 fish 2	32 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 2	27 mg/l (24 h; Daphnia magna)
TLM fish 1	25.1 mg/l (96 h; Lepomis macrochirus; SOFT WATER)
TLM fish 2	46.4 mg/l (96 h; Pimephales promelas; SOFT WATER)
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit other aquatic organisms 1	10 - 100,96 h; Pseudomonas putida
Threshold limit other aquatic organisms 2	72 mg/l
Threshold limit algae 1	> 200 mg/l (192 h; Scenedesmus quadricauda; INHIBITORY)
Threshold limit algae 2	67 mg/l (Microcystis aeruginosa; INHIBITORY)

12.2. Persistence and degradability

Composite Resource Marine Laminating Resin (Mixture)	
Persistence and degradability	Not established.
styrene, inhibited (100-42-5)	
Persistence and degradability	Readily biodegradable in water. Not readily biodegradable in water. Forming sediments in water. Non degradable in the soil. Adsorbs into the soil. Photodegradation in the air. Not established.
Chemical oxygen demand (COD)	2.80 g O ² /g substance
ThOD	3.07 g O ² /g substance
BOD (% of ThOD)	0.42 % ThOD
Proprietary Resin (Proprietary)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Composite Resource Marine Laminating Resin (Mixture)	
Bioaccumulative potential	Not established.
styrene, inhibited (100-42-5)	
BCF fish 1	12 - 77 (QSAR)
BCF fish 2	35.5 (Carassius auratus)
Log Pow	2.95 - 3.16 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
Proprietary Resin (Proprietary)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

styrene, inhibited (100-42-5)	
Surface tension	0.032 N/m (19 °C)

12.5. Other adverse effects

Other information : Avoid release to the environment.

Composite Resource Marine Laminating Resin

Safety Data Sheet CR3010MA Marine Laminating

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT
UN-No.(DOT) : UN1866
DOT Proper Shipping Name : RESIN SOLUTION
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN UN1866 RESIN SOLUTION, III
Packing group (ADR) : III

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Composite Resource Marine Laminating Resin (Mixture)

RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
--	---------

styrene, inhibited (100-42-5)

RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Reactive hazard Fire hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Composite Resource Marine Laminating Resin

Safety Data Sheet CR3010MA Marine Laminating

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

styrene, inhibited (100-42-5)

Listed on EPA's Hazardous Air Pollutants (HAPS)

15.3. US State regulations

Composite Resource Marine Laminating Resin(Mixture)

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS) U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
----------------------------	---

styrene, inhibited (100-42-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)

styrene, inhibited (100-42-5)

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H224	Extremely flammable liquid and vapour
H226	Flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H351	Suspected of causing cancer

SDS US (GHS HazCom 2012)

To the best of our knowledge this SDS is accurate. The the extent allowed by law, this statement is made in lieu of an other warranties, expressed or implied including but not limited to any implied warranty of merchantability or fitness for a particular purpose and is in lieu of any other obligations or liability on the part of Dura Technologies, Inc.